

HORDGTLCO2

CO2 sensor multifunctional LED - Time/temperature/humidity



No information escapes you, the time, temperature, humidity or air quality of your workspaces, our clock tells you everything !


Informes about the air quality
CO2 indicator via NDIR sensor
(non-dispersive infrared sensor)



Sound alarm customizable according to
the desired CO2 detection threshold,
(possibility to deactivate it)



Temperature
and humidity




Time display



be fixed to the wall or
be placed on a table



Works with 1 adaptator (supplied)
+ 2 LR6 memory battery (supplied)



Following the regulatory framework for monitoring indoor air quality in institutions (Decree No. 2015-1000 of August 17, 2015) and the latest recommendations recommended by the High Council of Public Health on ventilation and aeration of establishments open to the public in the context of the Covid-19 pandemic, it is strongly recommended to equip yourself with a CO2 sensor in order to measure the concentration of carbon dioxide (CO2) in the air and to act quickly in case of strong pollution in the room.

HORDGTLCO2




CO2 sensor multifunctional LED - Time/temperature/humidity







No information escapes you, the time, temperature, humidity or air quality of your workspaces, our clock tells you everything !

TECHNICAL FEATURES	
Reference	HORDGTLCO2
EAN	3129710017553
Materials	Frame : ABS / Lens : ABS / LED display : White
Colour	Frame : Black / Number : White
Product dimensions	L 37.5 x W 13.5 x Th 3.8 cm
	Weight : 0.650 kg
Visibility	Visibility of the time up to 30 m, height of digits: 5.8 cm
Mechanism	Electronic - Silent and precise
Data available	Time : Hour - min (24H or 12H format)
	Temperature : -9°C to +85°C (Celsius or Fahrenheit)
	Humidity : 0% to 100% RH
	CO2 : NDIR Sensor (Non-Dispersive Infrared Sensor) Automatic or manual calibration / Accuracy 1 ppm. Visual indicator (coloured sheet) for measurement (see table below)
Alarm	Yes - customisable to the desired CO2 detection threshold, can be disabled.
Battery	Works with 1 adapter (cable: 180 cm) (supplied) + 2 LR6 memory batteries (supplied)
Mounting	Wall or table
Origin	French design and development - Manufacturing in PRC
Norms	ROHS - CE
Guarantee	3 years

DIMENSIONS PACKAGING	
* Sales unit (x1SU) Box	Dim. : L. 37,5 cm x W. 4 cm x H. 13,6 cm
	Weight : 0.890 kg
* Box master (x10SU)	Dim. : L. 65 cm x W. 42 cm x H. 20 cm
	Weight : 9.89 kg



Measures	Colour of the leaf 	Air quality
0 to 799 ppm	Green 	Good
800 to 1199 ppm	Orange 	Medium
1200 to 1599 ppm	Red 	Bad



Quand le beau rejoint l'utile

